

# Automatic Level

## 32x & $\pm 1.0\text{mm}$ Air Damping

- Magnification: 32x
- Accuracy:  $\pm 1.0\text{mm}$
- Multi-coated Objective Aperture: 40mm
- Air Damping Compensator
- IP54, w.Plumb Bob/Plastic Case
- w. 5/8" Thread for all Surveying Tripods

# SURWAY

# NA32



## 32x

Telescope

## Specifications

Magnification	32x
Accuracy (Standard Deviation for 1Km Double-Run Leveling)	$\pm 1.0\text{mm}$ (without Micrometer)
Objective Aperture	40mm
Image of Telescope	Erect
Length of Telescope (from Objective to Eyepiece)	--
Shortest Focusing Distance	0.40m
Field of View	1°20'
Setting Accuracy	$\pm 0.3''$
Setting Time	$\leq 2''$
Resolution Power	6"
Compensator Type	Air Damping
Working Range	$\pm 15''$
Multiplication Constant	100
Additive Constant	0
Sensitivity of Circular Level	8'/2mm
Horizontal Outer Circle	360°/1°; 400gon/1gon available
Ambient Temperature	-20°C ~ +45°C



## Features

- Replacement of Automatic Level NA32
- Multi-coated Objective Lens producing HD Image
- Robust Outer Circle for easy and fast reading
- Equipped with Check Button for protecting, checking and controlling Compensator
- Metal-house Circular Bubble offering high precision and great stability
- IP54, shock-resistant, dust-tight and water-proof for rough working conditions
- Standard Accessories : Adjusting Pin, Desiccating Agent, Hex Key, Plumb Bob, User Manual
- Recommended Staff : Please refer to "Leveling Rods & Bipods"
- Recommended Tripod : Please refer to "Surveying Tripods"



บริษัท เอส.ดี.เอ็ม. จำกัด

1/285 หมู่ 9 ต.บางพลู อ.ปากเกร็ด จ.นนทบุรี 11120

โทร. 02 582 3509 Line id : @SDMthailand

www.sdm.co.th